

# Glossary of Terms – Seal Team Fix

## **Apparatus / System**

A combined physical device or configuration of components designed to seal a large **conduit** under emergency conditions. This includes sealing, conveyance, anchoring, and removal elements.

---

## **Conduit**

The interior water passage within a Reclamation dam facility. It channels water between the upstream and downstream sides of a structure and may be round, rectangular, or transitional in shape. Conduits are typically concrete- or steel-lined.

---

## **Deployment**

One of the four core engineering functions. Describes how the sealing system is transported from the surface (e.g., dam crest, vessel) to the **inlet** of the **conduit**.

---

## **Differential Pressure**

The difference in water pressure between the upstream (US) and downstream (DS) sides of a sealing solution. Effective solutions may/could harness this pressure differential to help seat or anchor the sealing device against the flow.

---

## **Downstream (DS)**

The outlet end of the conduit, where water discharges after passing through the structure. This side typically has lower pressure during an uncontrolled release.

---

## **Gate**

A closure device in which a leaf or closure member is moved across the fluidway from an external position to control the flow of water.

---

## **High-Head Condition**

A scenario in which the pressure exerted on the conduit (measured as feet of water head) is significant, typically defined as **up to 200 ft** in this challenge. Some Reclamation sites may experience even higher head pressures (e.g., 250–300+ ft).

---

## **Inlet**

The entrance of the conduit on the upstream side. The inlet may differ in shape from the conduit itself (e.g., square or rectangular inlet leading to a round conduit) and serves as a potential mating surface for sealing devices. It may be equipped with **trash racks**.

---

---

**Installation Time**

The time required to position and fully deploy the sealing system once it arrives on-site. Measured in **hours**. Distinct from total deployment time, which includes transport or logistics.

---

**No Diver Intervention**

A challenge requirement indicating that human divers must not be required for any phase of the system's deployment or removal.

---

**Obstructing Flow**

One of the four core engineering functions. Refers to how the proposed solution physically stops or reduces the flow of water through the conduit during an uncontrolled release.

---

**Seal Effectiveness**

A measure of how well a system reduces flow through the conduit during an emergency. The target is **95–98% reduction** of uncontrolled flow, typically evaluated by total conduit capacity less the measured leakage in the conduit.

---

**Sealing Performance**

One of the four core engineering functions. Describes how the seal is maintained in place for the required duration, resisting forces from flow and pressure without shifting, degrading, or dislodging.

---

**System Removal**

One of the four core engineering functions. Describes how the system is deactivated or extracted after its temporary use.

---

**Temporary Seal**

A sealing solution that is designed to remain in place for a limited duration, typically several months, long enough to allow safe upstream isolation or repair. It is not a permanent fixture.

---

**Trash Rack**

A structural grate at the conduit inlet designed to block large debris from entering the conduit, which could interfere with sealing system placement and adherence/bearing load. Trash racks have some offset from the inlet opening, typically several feet or more.

---

**Upstream (US)**

The intake side of the conduit. This side typically has higher water pressure and is the origin point of flow during normal operation or gate failure.

---

**Valve**

A mechanical component (distinct from a “gate”) that regulates, controls, or stops water flow. Valve types include cone valves, sleeve valves, and needle valves. In some Reclamation facilities, conduit sealing is required when valves cannot isolate flow.